

OLYMPUS®

CAMEDIA® D-560 ZOOM Powerful 3x optical/ 10x total zoom with aspherical glass elements. High-quality 3.2 megapixel CCD. Exclusive TruePic™ technology and more. All in a compact, stylish camera packed with features that make great photos easy. Four scene program modes. Software-free Auto-Connect USB downloading. And everything else you need for the most realistic digital images yet. Nothing's impossible.



olympusamerica.com/d-560

Powerful, Sophisticated Zoom A high-power, high-quality Olympus 3x optical zoom lens with aspherical glass elements gives you pictures filled with sharp detail. And a 3.4x digital zoom gives you the flexibility of a 10x total seamless zoom.

3.2 Megapixel CCD (Effective) Shoot big images perfect for sharp, detailed prints 8" x 10" and larger, or small images ready to e-mail. Enjoy total photographic flexibility.

Four Scene Programs Portrait mode for enhanced skin tones. Landscape mode for richer blues and greens. Shoot like an expert with four easy-to-use scene programs.

Compact, Elegant Design From surprise parties to last-minute getaways, the small and stylish D-560 Zoom commands attention everywhere it goes.

TruePic™ An exclusive Olympus technology that creates every image using every pixel, so even pictures shot at low resolution settings are sharp and clear.

Auto-Connect USB Nearly any computer with a USB port will recognize the D-560 Zoom and connect automatically. No software. No hassle.

QuickTime® Movies With the D-560 Zoom, you're always ready to shoot a video that's easy to e-mail or watch on almost any TV. The hula dance never looked so good.

Packed with Features Multi-mode flash, auto white balance and an intuitive menu navigation system. Panorama, sequence and 2-in-1 picture modes. The D-560 Zoom is packed with the most innovative features for the most beautiful photos.

► With our exclusive TruePic™ technology, you don't always have to shoot at high-resolution settings to get pictures filled with sharp detail and vibrant color.



Megapixel 3.2 Effective	Optical 3x Zoom	Seamless Zoom 10x Optical & Digital	TruePic™ Pixel Smoothing	Auto-Connect USB	Picture Card™ xD Compatible	QuickTime® Movie Mode
--------------------------------------	------------------------------	--	-----------------------------	----------------------------	-----------------------------------	--------------------------



D-560 ZOOM Specifications

Stock No. 225380

CCD Imager	3.2 megapixel effective 3.3 megapixel gross 1/2.5" (0.4") CCD
Lens	Olympus 3 aspherical glass zoom lens 5.8 – 17.4mm (35 – 105mm equivalent in 35mm photography), 5 lenses in 3 groups
Digital Zoom	Seamless to 10x (3x optical and 3.4x digital combined)
Aperture Range	f3.0 – f5.2
Shutter Speeds	1/1000 sec. – 2 sec.
ISO	Auto, 60 – 400 (equivalent)
Recording Modes	Still image: EXIF 2.2 JPEG, DCF (Design rule for Camera File system), PRINT Image Matching II Movie mode: QuickTime motion JPEG
Adjustable Resolutions	2048 x 1536 JPEG (SHQ, HQ) 1024 x 768 JPEG SQ1 640 x 480 JPEG SQ2
QuickTime Movie	15 sec. at 15 fps in 320 x 240 HQ mode 60 sec. at 15 fps in 160 x 120 SQ mode
TruePic™	Uses all pixels at all resolutions, Pixel micro-smoothing
Noise Reduction	Mode available at shutter speeds of 1 second or longer
Pixel Mapping	Automatic Pixel Mapping (APM) available via menu setting
DPOF (Digital Print Order Format)	Print reserve (single, all, number of copies), Cropping, Date or time
Image Shooting Effects	2-in-1 picture mode
Image Edit Effects	Black and white, Sepia, Resize, Rotation
Panorama	Up to 10 frames automatically stitchable with CAMEDIA Master software when using Olympus brand xD-Picture Card™
Sequence	1.5 frames per second burst up to 5 frames in HQ mode
Viewfinder	Optical real-image viewfinder
LCD	1.8" (4.5 cm) amorphous silicon LCD (approx. 85,000 pixels)
Focusing System	iESP multi-pattern TTL autofocus system
Focusing Ranges	Normal mode: 32" (0.8 m) – infinity Macro mode: 8" – 32" (0.2 m – 0.8m)
Exposure Compensation	±2 steps EV in 1/2 EV steps
Scene Programs	Portrait, Self-portrait, Landscape, Night scene

Metering System	Digital ESP multi-pattern, Spot
White Balance System	iESP multi-pattern auto TTL, Pre-set manual (Daylight, Overcast, Tungsten and Fluorescent)
Flash	Built-in flash
Flash Modes	Auto for low and backlight Red-Eye Reduction Fill-In Slow Shutter Synchronized (1st curtain and 1st curtain with Red Eye Reduction) Off
Flash Working Range	Wide: 8" – 7' (.2 m – 2.1 m), Tele: 8" – 6.7' (.2 m – 2.0 m)
Flash Charging Time	Approx. 6 seconds at normal temperature with fully charged battery
Removable Media	3V (3.3V) xD-Picture Card, 16MB card included
Selftimer	12-second delay
Settings Memorization	On/Off (Hold changes/Reset to default settings)
Outer Connectors	USB connector (Auto-Connect), Video out, DC input
Auto-Connect USB	Compatible with Windows 98 rev2/ME/2000 Pro/XP and Mac OS 8.6 – OS X and higher Windows 98 rev2 driver provided on CD Mac OS 8.6 requires USB mass storage driver 1.3.5 available at apple.com Downloading to laptop computer without USB port possible with optional PCMCIA xD-Picture Card™ reader
Image Playback	Still image: Index display, up to 4x enlargement, Slide show, Scene rotation Movie: Normal, Frame-by-frame
Operating Environment	Operation: 32° – 104°F (0° – 40°C) 30 – 90% humidity Storage: -4° – 140°F (-20° – 60°C) 10 – 90% humidity
Power Supply	2 x AA alkaline batteries (included) 1 x LB-01 (CR-V3) lithium battery pack 2 x AA NiMH rechargeable 2 x AA NiCd rechargeable (Manganese batteries cannot be used) AC Power: E-7AU AC adapter (optional)
Date/Time Calendar	Simultaneous recording into image data, Automatic up to year 2099
Size	4.2" W x 2.3" H x 1.6" D (108 x 57 x 40 mm) excluding protrusions
Weight	5.6 oz. (170 g) without battery and media card

Available Accessories

Product Number	UPC 050332-	Accessory
200728	123502	B-01 4PE NiMH Battery (4 Battery Cells)
200800	295759	B-50SU Fast NiMH Battery and Charger Set
200795	295742	B-60SU Overnight NiMH Battery and Charger Set
200656	131347	LB-01 2PU CR-V3 Lithium Battery 2-Pack
200751	295223	E-7AU 110V AC Adapter Blister Pack
200803	296305	MAUSB-5W SmartMedia/CompactFlash™ USB Reader/Writer
200830	139138	MAUSB-10 xD-Picture Card/SmartMedia USB Reader/Writer
200837	139512	MACF-10 xD-Picture Card/CompactFlash Adapter
200835	139145	MAPC-10 xD-Picture Card/SmartMedia PCMCIA/PC Card Adapter
200840	139084	xD-Picture Card 16MB
200841	139091	xD-Picture Card 32MB
200842	139107	xD-Picture Card 64MB
200843	139114	xD-Picture Card 128MB
200844	139565	xD-Picture Card 256MB
200776	136205	CB-USB4 Digital Camera USB Cable (replacement)
200529	124004	CB-VC1 Digital Camera Video Cable (replacement)
200784	295643	Digital Camera Gadget Bag
200806	296053	D-Series 2 year Extended Warranty

Memory Card Storage Capacity

Quality	Pixel Resolution	16MB xD-Picture Card (included)	256MB xD-Picture Card
SHQ	2048 x 1536	6 shots	96 shots
HQ	2048 x 1536	20 shots	320 shots
SQ1	1024 x 768	76 shots	1216 shots
SQ2	640 x 480	165 shots	2640 shots
HQ	320 x 240 15 fps movie	15 sec. max per movie	15 sec. max per movie
SQ	160 x 120 15 fps movie	60 sec. max per movie	60 sec. max per movie

All capacity figures are approximate.

Package Contents

- CAMEDIA D-560 Zoom Digital Camera
- 16MB xD-Picture Card™
- Digital Camera Win/Mac USB Cable
- (2) AA Alkaline Batteries
- Video Cable
- Wrist Strap
- Quick Start Guide
- Printed Instruction Manual
- Warranty Card
- CD-ROM: CAMEDIA Master Software, Windows 98 Rev 2 Driver, Camera Reference Manual